

## Shupe Run Streambank Restoration

**Design Features:** riparian buffer, stone deflectors, single log vane deflectors, regrading of streambank, rip-rap, rock toes

**Date of Installation:** Phase I: 2008, Phase II: 2013

**Location:** Willow Park, Center Ave.,  
Mt. Pleasant, PA 15666

**Client:** Mt. Pleasant Borough

**Cost:** \$103,000

**Project Partners:** Westmoreland Conservation District, Jacobs Creek Watershed Association, Mt. Pleasant Borough, Mt. Pleasant Township

**Project Contact:** Rob Cronauer  
Rob@wcdpa.com

### Project Specifications

The area of Shupe Run in Willow Park near the soccer fields was severely eroding due to the high flows of stormwater entering the stream during rain events, which was threatening the fence and nearby soccer fields next to the stream. This had caused the banks of the area to become almost vertical with little to no vegetated buffer to help control the erosion.

The Westmoreland Conservation District provided technical assistance and project management for this project. Funds were acquired from two sources for the two phases of the project. Phase I was funded by a Growing Greener grant, and Phase II was funded by an EPA Section 319 grant. Both were used to implement Best Management Practices (BMPs) to stabilize the streambank and reduce the amount of sediment entering the stream.

Phase I of this project was completed in the spring of 2008 and consisted of a number of BMPS. Large amounts of rip-rap and rock toes were placed along sections of the bank to reduce erosion. The steepest parts of the streambank were graded down to a shallower angle. Riparian buffers were planted all along the project area to stabilize the eroding streambank.



*Severe erosion threatening the soccer fields' fence next to Shupe Run*



*Stabilized bank under fence after rip-rap and riparian buffer planting*

Phase II was completed in March of 2013 and built upon the previous work done in 2008. Stone deflectors, rock toes, and single log vanes were installed at five areas along Shupe Run, along with additional streambank grading and riparian buffers.

### Benefits

The installation of the various BMPs along Shupe Run stabilized 2,000+ feet of streambank, cooled water temperatures to create better aquatic habitats for fish, and prevented around 33,000 pounds of sediment entering the stream per year.

## Shupe Run Streambank Restoration



*Streambank before construction*



*Streambank a few months after construction*



*Streambank seven years after construction.  
Note the amount of vegetation that has grown up*

Shupe Run Streambank Restoration



*Eroding bank near pedestrian bridge*



*Bank shortly after grading, rip-rap, and seed and mulch*



*Bank seven years after BMPs were installed*

## Shupe Run Streambank Restoration



*A section of Phase II streambank before construction*



*Phase II streambank after construction*



*Another Phase II streambank section before construction*



*The same section after construction*